



**HOSEBED CAPACITIES**

- 300' OF 1.75" DJP HOSE
- 150' OF 1.75" DJP HOSE
- 900' OF 5.00" DJP HOSE
- 300' OF 2.50" DJP HOSE
- 200' OF 2.50" DJP HOSE
- 200' OF 2.50" DJP HOSE
- 300' OF 1.75" DJP HOSE

ALUMINUM BODY    MAXIMUM O.A.L. 388.00"    MAXIMUM O.A.H. 124.00"    SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- AIR INLET/OUTLET WITH DISCONNECT FITTING LOCATED IN DRIVER'S SIDE STEPWELL
- AIR OUTLET WITH SHUT OFF VALVE LOCATED AT DRIVER'S SIDE PUMP PANEL
- BATTERY CHARGER MOUNTED BEHIND DRIVER'S SEAT
- BATTERY CHARGE INDICATOR LOCATED NEAR DRIVER'S SEAT RISER WITH BRACKET
- SHORELINE RECEPTACLE WITH KUSMAUL SUPER AUTO-EJECT LOCATED IN DRIVER'S SIDE STEPWELL

REV	DATE	BY	CH	VELOCITY
1	21JAN25	SAM	CSH	CHASSIS DATA
2	01JUL24	SAM	ZWE	MAKE
3	29MAY24	SAM	ZWE	PIERCE
4	05APR24	SAM	WKL	MODEL

**Pierce MANUFACTURING INC.**

JOB NO. 38759 01-02  
 SCALE 1:24 DATE  
 DRAWN BY SAM 29MAR24  
 CHECKED BY WKL 29MAR24  
 SHEET SIZE D SHEET NO. 1 OF 2

TITLE 1500GPM, 520G TANK, 500G WATER, 20G FOAM  
 152" PUMPER BODY, MUX  
 FOR TURLOCK FIRE DEPARTMENT  
 TURLOCK, CALIFORNIA  
 DWG NO. 38759AD-SH1