



- HOSEBED CAPACITIES
- ① 250' OF 2.50" D.J. POLY HOSE
 - ② 250' OF 2.50" D.J. POLY HOSE
 - ③ 400' OF 2.50" D.J. POLY HOSE
 - ④ 400' OF 2.50" D.J. POLY HOSE
 - ⑤ 1000' OF 5.00" D.J. POLY HOSE

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- 2. AIR INLET/OUTLET WITH DISCONNECT FITTING ON D.S. PUMP PANEL
- 3. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT

REV	DATE	BY	CH	ENFORCER
7AUG24	JWR	CSH		
27JUN24	JWR	CSH		
12APR24	CDU	SJS		

		JOB NO.	38898
		SCALE	1:24
TITLE 1500GPM, 750G TANK, 710G WATER, 40G FOAM CELL 152" PUMPER, HARD WIRED		DRAWN BY	JWR
		CHECKED BY	CDU
FOR CITY OF LYNCHBURG LYNCHBURG, VIRGINIA		SHEET SIZE	D
		SHEET NO.	1 OF 1
DWG NO.		38898AD	