



- HOSEBED CAPACITIES**
- ① - 1200' OF 4.00" D.J. POLY HOSE
 - ② - 200' OF 2.50" D.J. POLY HOSE (PRECONNECTED)
 - ③ - 500' OF 3.00" D.J. POLY HOSE

ALUMINUM BODY SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. AIR INLET WITH DISCONNECT FITTING LOCATED PER ORDER
- 2. BATTERY CHARGER LOCATED PER ORDER
- 3. BATTERY CHARGER INDICATOR DISPLAY LOCATED PER ORDER

REV	DATE	BY	CH	VELOCITY FR
02MAY24	JJB	JLL		
28MAR24	JJB	JLL		

MANUFACTURING INC.		JOB NO.	38942
		SCALE	DATE
TITLE 2000 GPM, 770G TANK, 750G WATER, 20G FOAM 152" PUMPER BODY, VELOCITY ESP	FOR SAND SPRINGS OKLAHOMA FIRE DEPARTMENT SAND SPRINGS, OK	DRAWN BY	JJB
		CHECKED BY	SJS
DWG NO. 38942AD	SHEET NO. 1 OF 1	SHEET SIZE	