



- HOSEBED CAPACITIES**
- ① - 300' OF 2.50" D.J. POLY HOSE
 - ② - 1000' OF 5.00" RUBBER HOSE
 - ③ - 150' OF 3.00" D.J. POLY HOSE
 - ④ - 150' OF 3.00" D.J. POLY HOSE
 - ⑤ - OPEN HOSE BED

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. BATTERY CHARGER LOCATED UNDER CENTER FORWARD FACING CREW CAB SEAT
- 2. ONE CATCH DRAINER ASSEMBLY IN COMPARTMENT L53
- 3. HERCULES 200 CFM COMPRESSED AIR FOAM SYSTEM

REV	DATE	BY	CH	VELOCITY FR
16JUL24	SJM	DTJ		
06JUN24	SJM	DTJ		
11APR24	JJB	WKL		

		JOB NO.	38950
		SCALE	DATE
TITLE	2000 GPM, 770G TANK, 750G WATER, 20G FOAM 152" 2G PUMPER, MUX	DRAWN BY	JJB
FOR	BEXAR BULVERDE VOLUNTEER FIRE DEPARTMENT SAN ANTONIO, TEXAS	CHECKED BY	WKL
DWG NO.	38950AD	SHEET SIZE	SHEET NO.
		D	1 OF 1